



Residual current operated circuit breaker, 4-pole, type AC, In: 100 A, 30 mA, Un AC: 400 V

Model			
product brand name	SENTRON		
product designation	RCCB		
design of the product	Instantaneous		
General technical data			
number of poles	4		
Supply voltage			
supply voltage			
• at AC / rated value	400 V		
supply voltage frequency / rated value	50 Hz		
Current			
tripping fault current / rated value	30 mA		
operational current			
• at AC / rated value	100 A		
residual current type	AC		
Mechanical Design			
net weight	205 g		
<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>other</b>	<b>Dangerous Good</b>



[Miscellaneous](#)



[Miscellaneous](#)

[Transport Information](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SM3348-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SM3348-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SM3348-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM3348-0)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



