

Product data sheet

Specifications



32A Double Pole Switch with White LED, White

E3031DR32_EWWW

Main

Range	Neo
Wiring device mounting	Flush Surface
Switch function	2-pole
Switch application	Switch
Load type	Incandescent lamp Resistive Inductive
Bulb type	LED (white)
Colour tint	White

Complementary

Rated current	32 A at 250 V AC 50/60 Hz
Number of gangs	1 gang
Material	Polycarbonate: plastic part
Clamping connection capacity	1 x 23 mm ² for solid cable(s) 1 x 23 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Embedding depth	16.8 mm
Depth	28.3 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	75 g
Package 1 Height	22 mm
Package 1 width	86 mm
Package 1 Length	86 mm
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Weight	7500 g
Package 2 Height	205 mm
Package 2 width	415 mm
Package 2 Length	500 mm
Unit Type of Package 3	P12
Number of Units in Package 3	2000
Package 3 Weight	168000 g
Package 3 Height	1300 mm
Package 3 width	800 mm
Package 3 Length	1200 mm

Contractual warranty

Warranty	18 months
-----------------	-----------